ANDROID OS

Art. EL-104XAIO-T serie



MEETING ROOM

RoomBooking screen for reservation occupation status + Digital Signage features (logos / videos on screen). Occupation status is indicated OnScreen and LedLight color indication at the sides.

ONLINE MODELS

Reservation via Google Calendar, i-Cal Outlook



TOUCH & PANEL

- 10 points capacitive touch (or non touch panel)
- High Resolution Panel 1280x800
- 24-7 Usage



ANDROID CHIP & OS VERSIONS

- RK3288 with Android OS 8 or 10
- RK3399 with Android OS 9, 10 and 12
- RK3366 with Android OS 11



ADDITIONAL FEATURES:

- PoE: Power over Ethernet (8 to 21.5inch)
- NFC & RFID (optional)
- Triggering: pushbuttons, sensors
- LED light: external lightstrips

Note: There is no roombooking software installed, please provide your own software or we can provide software.

ANDROID ROOTED

All our models have Rooted Android. The OS system can be adjusted according your needs.

YOUR SOFTWARE

We can pre-install your software apps on the Android OS. We can also make your OS image custommade, with your startup logo.



Easy hangup system at backside (VESA Scew holes plate)



AutoStart by plug in power adapter



WIFI and LAN for internet connection (optional SIM USB dongle)

Certifications:



SOFTWARE OPTIONS

ADD: YOUR SOFTWARE

We can pre-install your software apps on the Android OS. We can also make your OS image custommade, with your startup logo.

ADD: SIGNAGE SOFTWARE

We can pre-install software apps on the Android OS. Find some suggestions below:

KIOWARE: Lockdown your website or App.

FULLY VIDEO: AutoLoop Video from USB stick/Internal Memory **FULLY WEBSITE:** Lockdown your website.

SIGN CONTROLL: Digital Signage with remote controlled pushed presentations with webbased controll system. Create in the CMS presentations and schedule them, online.

Add: external Triggers & Sensors for Video Activation

Optional, Android screens with external triggers and sensors.

We can customize Android displays in the factory for:

- Metal or Plastic Pushbuttons with Lightring and symbols
- Touchless sensor buttons to activate a video
- RFID Sensors for Lift and Learn
- RFID for "Scan for info"
- Motion detection sensors
- Light Sensor detection area

Add: (Interactive) LED Light strips and panels

Android screens with external LED strips or LED Panels

We can customize Android displays in the factory for:

- LED strips or LED Panel Light up your product
- Light up your product during a video
- Light up your Display Logo
- Different colors





SPECIFICATIONS:

Model article number			EL-1042AIO-T			EL-1043AIO-T		EL-1046AIO-T	EL-1046AIO-T	
CPU			RK3288; Quad-core cortex A17,1.8G			RK3399; [Dual-core A72+quad-core A53,1.8G	RK3566; Quad core cortex A55		
RAM		2GB		2GB		2GB	Optional 4GB			
Internal memory		16GB		16GB		16GB	Optional 32GB/64GE			
peration	system		Android 8.1/10			Android 9.	0/10	Android 11	•	
peration	system									
		Touch screer	1		10-Point capacit	ive touch				
		Panel			10.1" LCD panel					
		Resolution			1280*800					
Dis	play	Luminance			250cd/m2					
		Display mode			Normally black					
		Viewing angle			85/85/85/85(L/R/U/D)					
		Aspect Ratio		16:10						
		WiFi		802.11b/g/n						
Network		Ethernet		100M/1000M ethemet						
		Buletooth		Bluetooth 4.0						
		Card slot			SD card, Max support to 64GB					
		SIM Slot - 4G module		4G Flow card (optional, not included!)						
		USB		USB host						
		Micro USB			Micro USB OTG					
Interface	rface	USB			USB for serial (RS232 format / TTL level)					
		RJ45 with POE			RJ45 input with PoE (optional) PoE: IEEE802.3at, POE+, class 4, 25.5W					
		Power jack			DC power input					
		Earphone		3.5mm earphone + Micphone						
		Video format		MPEG-1,MPEG-2,MPEG-4,H.263,H.264,VC1,RV etc.,support up to 4K						
Media play Other		Audio format		MPEG-1,MPEG-2,MPEG-4, n.203, n.204, VC1, RV etc., support up to 4K						
		Photo								
		VESA		jpeg 75x75mm						
		Microphone			Built-in single microphone					
		Speaker		2*3W						
		LED Light bar		LED Light bar, RGB						
		RFID		Optional: 125k,ISO/IEC 11784/11785, Support to EM4100, TK4100/GK4100, EM4305, T5577						
		NFC		Optional: 125k,ISO/IEC 11784/11785, Support to EM4100, TK4100/GK4100, EM4305, 15577						
		Camera			Wide-angle 2.0M/P, front camera					
		Working temp			0-40degree					
		Certificates			CE/FCC					
		Language		Multi-language						
		Adapter			Adapter,12V/1.5A					
Accessories		User manual			Ves					
					1					
roduct M	leasuremen	t, mm	-					_		
Init (Witho	out packagin		Giftbox (W		Carton 10pcs/C			_		
L	W	Н	L	Н	L	W	Н			
255.8mm	175.8mm	31.7mm	320mm	mm	mm	mm	mm			
let(kg)	kg		Net(kg)		Net	kg		4		
					0.14					
					G.W					

ANDROID OS

SD Card


G-BSU

Mic

010

0

DRAWING:





\equiv ROOM SERIES

ANDROID OS

Group/Event	Room	Start/End
DEH Company Annual Meeting Opening Session	Peachtree Ballroom	8:00 AM 9:00 AM
DEH Company Annual Meeting Lunch	Atlanta Ballroom	11:30 AM 1:00 PM
DEH Company Annual Meeting Afternoon Break Out Sessions	Second Floor Meeting Rooms	1:00 PM 4:00 PM
DEH Company Annual Meeting Opening Session	Peachtree Ballroom	8:00 AM 9:00 AM
DEH Company Annual Meeting Lunch	Atlanta Ballroom	11:30 AM 1:00 PM
55"	58' - 60'	


















OTHER MODEL TYPES

OPEN FRAME



NARROW BEZEL



STRETCHED LCD



ROOM BOOKING



HEALTH CARE

DESK SHAPE



FLOOR KIOSK



HANGING LCD

