

MEETING ROOM

RoomBooking screen for reservation occupation status + Digital Signage features (logos / videos on screen). Occupation status is indicated OnScreen and LedLight color indication at the sides.

ONLINE MODELS

Reservation via Google Calendar, i-Cal Outlook



TOUCH & PANEL

- 10 points capacitive touch (or non touch panel)
- 13,3 inch High Resolution Panel 1920x1080
- 24-7 Usage



ANDROID CHIP & OS VERSIONS

- RK3288 with Android OS 8 or 10
- RK3399 with Android OS 9, 10 and 12
- RK3366 with Android OS 11



ADDITIONAL FEATURES:

- PoE: Power over Ethernet (8 to 21.5inch)
- NFC & RFID (optional)
- Triggering: pushbuttons, sensors
- LED light: external lightstrips

Note: There is no roombooking software installed, please provide your own software or we can provide software.

ANDROID ROOTED

All our models have Rooted Android. The OS system can be adjusted according your needs.

YOUR SOFTWARE

We can pre-install your software apps on the Android OS. We can also make your OS image custommade, with your startup logo.



Easy hangup system at backside (VESA Screw holes plate)



AutoStart by plug in power adapter



WIFI and LAN for internet connection (optional SIM USB dongle)

Certifications:



SOFTWARE OPTIONS

ADD: YOUR SOFTWARE

We can pre-install your software apps on the Android OS. We can also make your OS image custommade, with your startup logo.

ADD: SIGNAGE SOFTWARE

We can pre-install software apps on the Android OS. Find some suggestions below:

KIOWARE: Lockdown your website or App.

FULLY VIDEO: AutoLoop Video from USB stick/Internal Memory

FULLY WEBSITE: Lockdown your website.

SIGN CONTROLL: Digital Signage with remote controlled pushed presentations with webbased controll system. Create in the CMS presentations and schedule them, online.

Add: external Triggers & Sensors for Video Activation

Optional, Android screens with external triggers and sensors.

We can customize Android displays in the factory for:

- **Metal or Plastic Pushbuttons with Lightring and symbols**
- **Touchless sensor buttons to activate a video**
- **RFID Sensors for Lift and Learn**
- **RFID for "Scan for info"**
- **Motion detection sensors**
- **Light Sensor detection area**



Add: (Interactive) LED Light strips and panels

Android screens with external LED strips or LED Panels


We can customize Android displays in the factory for:




- **LED strips or LED Panel Light up your product**
- **Light up your product during a video**
- **Light up your Display Logo**
- **Different colors**



System	CPU	RK3566 Quad core cortex A55						
	RAM	2GB Optional 4GB						
	Internal memory	16GB Optional 32GB/64GB						
	Operation system	Android 11						
Display	Touch screen	10-Point capacitive touch						
	Panel	13.3"LCD panel						
	Panel Type	IPS						
	Resolution	1920*1080						
	Display Colors	16.7M Colors						
	Viewing angle	R/L 85/85, U/D 85/85						
	Display mode	Normally black						
	Contrast ratio	1500:1						
	Response Time	30ms						
	Back-light Type	ELed						
	Luminance	300cd/m2						
Aspect Ratio	16:9							
Network	WiFi	IEEE 802.11a/b/g/n/ac						
	Buletooth	Bluetooth 5.4						
	Ethernet	10M/100M/1000M ethernet						
Interface	SIM Slot	4G Flow Card						
	SD Slot	SD card ,Max support to 64GB						
	Earphone	3.5mm earphone + Microphone						
	USB	USB 3.0 host						
	USB	USB for serial (RS232 Level) , Optional USB Host						
	RJ45	Ethernet interface						
	Micro USB	Micro USB OTG						
	Power jack	DC power input						
Media play	Video format	MPEG-1,MPEG-2,MPEG-4,H.265,H.264,H.263,VC-1,VP8,VP9,MVC, etc.support up to 4K						
	Audio format	MP3/WMA/AAC/WAV/OGG, etc						
	Photo	JPEG/PNG/GIF,etc						
Other	v	White/Black						
	VESA	75x75mm						
	Button	Power						
	G-sensor	Support 90 degrees						
	Speaker	2*3W						
	Microphone	Single microphone						
	NFC	Optional, 13.56MHz, ISO/IEC 18092, ISO/IEC 21481, ISO/IEC 14443 A&B, ISO/IEC 15693, Japanese Industrial						
	RFID	Optional ,125k,ISO/IEC 11784/11785,支持EM4100, TK4100/GK4100						
	LED Light bar	LED Light bar, RGB						
	Camera	5.0MP with USB type						
	4G Moduel	Optional						
	Language	Multi-language						
	Certificates	CCC/CE/FCC						
	POE	Otional (Support IEEE802.3at,up to 30W)						
Working Surrounding	Working Temperature	0℃—40℃						
	Storage Temperature	-20℃—60℃						
	Working Humidity	20~80%RH						
	Storage Humidity	10~95%RH						
Accessories	Adapter	Adapter,12V/2A						
	User manual	*1						
Product Measurement, mm								
Unit (Without packaging)			Giftbox (With Packaging)			Carton 5pcs/CTN		
L	W	H	L	W	H	L	W	H
N.W(kg)			N.W(kg)			N.W(kg)		
						G.W		

DRAWING:








OTHER MODEL TYPES

OPEN FRAME



NARROW BEZEL




STRETCHED LCD



DESK SHAPE



ROOM BOOKING



HEALTH CARE



FLOOR KIOSK



HANGING LCD

