

# ANDROID (non)TOUCH DISPLAYS

## AVAILABLE SIZES:

**7 - 8 - 10 - 14 - 15.6 - 18.5 - 21.5 - 24 -  
27 - 32 - 43 - 55inch**



## RETAIL BUSINESS

Android Displays for use in a commercial environment. These displays have a rooted Android operating system and can be used for several solutions to inform and advise people in an attractive way, 24-7.

## ONLINE MODELS

Often used in retail displays and built-in ShopDisplays or in Public environments.



### TOUCH & PANEL

- 10 points capacitive touch
- Optional: non touch panel
- 14" High Resolution Panel 1920x1080 pixels
- 24-7 Usage



### ANDROID CHIP & OS VERSIONS

- RK3368 with Android OS 11 or 13
- RK3576S with Android OS 14



### ADDITIONAL FEATURES:

- PoE: Power over Ethernet (8 to 21.5inch)
- NFC & RFID (optional)
- Triggering: pushbuttons, sensors
- LED light: external lightstrips

### Note:

There is no signage software installed, please provide your own software or we can provide dedicated signage software.

## ANDROID ROOTED

All our models have Rooted Android. The OS system can be adjusted according your needs.

## YOUR SOFTWARE

We can pre-install your software apps on the Android OS. We can also make your OS image custommade, with your startup logo.



Easy hangup system at backside (VESA Screw holes plate)



AutoStart by plug in power adapter



WIFI and LAN for internet connection (optional SIM USB dongle)

### Certifications:



# SOFTWARE OPTIONS

## ADD: YOUR SOFTWARE

We can pre-install your software apps on the Android OS. We can also make your OS image custommade, with your startup logo.

## ADD: SIGNAGE SOFTWARE

We can provide software apps on the Android OS. Find some suggestions below:

**KIOWARE:** Lockdown your website or your app (kiosk mode)

**FULLY VIDEO:** AutoStart App loop video from USB & Internal Memory

**FULLY WEBSITE:** Lockdown your website in full screen mode

**SIGN CONTROL:** Remote controlled pushed presentations with web-based control system (CMS). Create in the CMS presentations and schedule them, online.

**ROOM & DESK SHARING:** Roombooking and Desk Sharing software

## Optional: add external Triggers & Sensors for Video Acti-

### Customized Android displays to connect triggers for video & volume activation:

- Metal or plastic pushbuttons with lighting and symbol
- Touchless sensor buttons (wave your hand above the sensor)
- RFID Sensors for “Lift and Learn”
- RFID Sensors for scanning a product with RFID sticker
- Motion detection sensors
- Light Sensors detection area



## Optional: add (Interactive) LED Light strips and panels

### Customized Android displays to connect LED lightning:

- LED strips or LED Panel Light up your product
- Light up a product during an activated video
- Light up a brand logo in a retail display
- Different colors available



## OPTIONAL DESK MOUNT:




# SPECIFICATIONS:

System	CPU	RK3576S Quad core cortex A53+Quad core cortex A72					
	RAM	4GB					
	Internal memory	64GB					
	Operation system	Android 14					
Display	Panel Size	14"LCD					
	Panel Type	IPS					
	Resolution	1920*1080					
	Display Colors	16.7M Colors					
	Color Gamut	45% NTSC					
	Viewing angle	R/L 85/85, U/D 85/85					
	Display mode	Normally black					
	Contrast ratio	700:1					
	Response Time	25ms					
	Back-light Type	ELed					
Touch	Luminance	250cdm2					
	Aspect Ratio	16:9					
	Model Type	Capacitive touch screen					
	Number of points	10-Point					
Network	WiFi	IEEE 802.11b/g/n/a/ac/ax (wifi 6)					
	Bluetooth	Bluetooth 5.3					
	Ethernet	10M/100M/1000M					
Interface	RJ45	Ethernet interface					
	USB	USB 2.0 Host					
	USB	USB 3.0 Host					
	Type-C	Only supports ADB function					
	HDMI IN	Support 800*600,1024*768,1280*720,1280*800,1280*1024,1366*768,1600*900,1920*1080, etc					
Media plays	Power Jack	DC power input					
	Video format	MPEG-1,MPEG-2,MPEG-4,H.265,H.264,H.263,VC-1,VP8,VP9,MVC, etc. support up to 4K					
	Audio format	MP3/WMA/AAC/WAV/OGG, etc					
Other	Photo	JPEG/PNG/GIF,etc					
	Product Colors	White/Black					
	VESA	100mm*100mm					
	Button	Power/Vol+/-Vol-					
	G-sensor	Support					
	Speaker	4Ω*3W*2					
	Microphone	Standard dual Microphone , Support noise reduction and echo cancellation					
	NFC	Optional , 13.56MHz, ISO/IEC 18092, ISO/IEC 21481, ISO/IEC 14443 A&B, ISO/IEC 15693, Japanese Industrial Standard (JIS)					
	Camera	Optional External USB type camera ( vertical portrait , 8.0MP with wide-angle and wide dynamic )					
	Language	Multi-language					
Working Surrounding	POE	Optional (IEEE802.3bt, up to 30W )					
	Certificates	CCC/CE/FCC					
	Working Temperature	0°C---40°C					
Accessories	Storage Temperature	-20°C---60°C					
	Working Humidity	20~80%RH					
	Storage Humidity	10~95%RH					
Accessories	Adapter	12V/2A					
	User manual	*1					
	Remote	Optional*1					



## DRAWING:



## OTHER MODEL TYPES

### OPEN FRAME



### NARROW BEZEL




### STRETCHED LCD



### DESK SHAPE



### ROOM BOOKING



### HEALTH CARE



### FLOOR KIOSK



### HANGING LCD

