## PRODUCT SHEET Android Counter Display 14inch Android Display Non Touch - OS8.1 - RK3288 ArtNr: EL-1412AIO-CD

#### MAIN FEATURES:

- Non Touch
- LCD panel 1920x1080 pixels
- Internal HD videoplayer 1080P
- CounterStand
- Rooted Android OS5.1/6.0/8.1
- Chip RK3288
- Internet access by WIFI + LAN (opt. 3G)
- Internal Speakers 2 x 1 W
- 3.5mm Jack output
- Thin housing
- USB host
- Power adapter with 3meter cable
- Usage up to 24 hours per day

#### MAIN PURPOSE:

- Digital Signage Display
- Advertisement Display
- Built-in ShopDisplays
- Kiosk Display
- CounterDisplay

#### USAGE:

This Android Display can be used in a commercial environment. The Display has Rooted Android operating. This professional display can be used for several solutions to inform / advise people in an attractive way.

#### SIGNAGE SOFTWARE:

We can provide several kinds of software apps to play your content, remotely controlled, like our "Signage App: control content by f.i. Dropbox and "SbEND signage.

#### OPTIONAL:


- We can install your software on the devices for larger order quantities.
- Internal Memory can be upgraded.
- Similar sizes available: 7 / 10.1 / 15.6 / 17.3inch.
- NFC RFID
- Internal Battery
- PoE Function







Internet access by:





Next pages: technical specs and drawing

All rights reserved. Changes to specifications and descriptions may be made at any time without prior notice.

### PRODUCT SHEET Android Counter Display 14inch Android Display Non Touch - OS8.1 - RK3288 ArtNr: EL-1412AIO-CD

#### SPECIFICATIONS:

nemory n system reen n ngle ratio re atio	2GB   16GB   Android 8.1   Non Touch   14"LCD panel   1920*1080   80/80/80/80   500   250cd/m2   ,16:9   802.11b/g/n   RJ45,100W1000M   Bluetooth 4.0   TF,support up to 32GB   USB slave   USB slave
n system reen n ngle ratio re atio	Android 8.1 Non Touch 14*LCD panel 1920*1080 80/80/80 800 250cd/m2 ,16:9 802.11b/g/n RJ45,100M/1000M Bluetooth 4.0 TF,support up to 32GB USB slave
n ngle ratio se atio	Non Touch     14*LCD panel     1920*1080     80/80/80     800     250cd/m2     ,16:9     802.11b/g/n     RJ45,100M/1000M     Bluetooth 4.0     TF,support up to 32GB     USB slave
n ngle ratio se atio	14"LCD panel   1920*1080   80/80/80/80   800   250cd/m2   ,16:9   802.11b/g/n   RJ45,100M/1000M   Bluetooth 4.0   TF,support up to 32GB   USB slave
n ngle ratio se atio	1920*1080 80/80/80/80 500 250cd/m2 ,16:9 802.11b/g/n RJ45,100M/1000M Bluetooth 4.0 TF,support up to 32GB USB slave
ngle ratio re atio	1920*1080 80/80/80/80 500 250cd/m2 ,16:9 802.11b/g/n RJ45,100M/1000M Bluetooth 4.0 TF,support up to 32GB USB slave
ngle ratio re atio	80/80/80/80 800 250cd/m2 ,16:9 802.11b/g/n RJ45,100M/1000M Bluetooth 4.0 TF,support up to 32GB USB slave
ratio ee atio	800     250cd/m2     ,16:9     802.11b/g/n     RJ45,100M/1000M     Bluetooth 4.0     TF,support up to 32GB     USB slave
atio	250cd/m2 ,16:9 802.11b/g/n RJ45,100M/1000M Bluetooth 4.0 TF,support up to 32GB USB slave
atio	,16:9 802.11b/g/n RJ45,100W/1000M Bluetooth 4.0 TF,support up to 32GB USB slave
	802.11b/g/n RJ45,100W/1000M Bluetooth 4.0 TF,support up to 32GB USB slave
	RJ45,100W/1000M Bluetooth 4.0 TF,support up to 32GB USB slave
	Bluetooth 4.0 TF,support up to 32GB USB slave
	USB slave
	USB slave
Interface	HDMI output,up to 4K
k	DC power input
)	3.5mm earphone with microphone
	USB type serial port(RS232)
RJ45	RJ45,100M/1000M (POE function, optional, IEEE802.3at)
mat	MPEG-1, MPEG-2, MPEG-4, H.263, H.264, VC1, RV etc., support up to 4K
mat	MP3/WMA/AAC etc.
	ipeg
	Optional ,NFC 13.56MHz, ISO14443A/ISO14443B/ISO 15693/Mifare classic/Sony felica
	Optional
Microphone	Microphone
	2*2W
	2.0M/P,front camera(optional Binocular camera)
9	Multi-language
-	White/black
	Adapter,12V/2A
ual	ves
	rt mat mat ne e

# PRODUCT SHEETAndroid Cou14inch Android Display Non Touch - OS8.1 - RK3288

## Android Counter Display

ArtNr: EL-1412AIO-CD

DRAWINGS:

