

PRODUCT SHEET

Android Display

24inch Android Touch Display - OS5.1 / 6.0 / 8.1 - RK3288

ArtNr: EL-2402AIO-T

MAIN FEATURES:

- Touch Screen
- AutoStart by plug in power-adapter
- LCD panel 1920*1080 pixels - IPS
- Internal HD videoplayer 1080P
- Rooted Android 5.1 / 6.0 / 8.1 - RK3288
- Internet access by WIFI / LAN (opt. 3G)
- Internal Speakers
- 3.5mm Jack output
- Thin housing
- Power adapter with 3meter cable
- Usage up to 24 hours per day
- ScrewHoles for hangup / built-in



MAIN PURPOSE:

- Digital Signage Display
- Advertisement Display
- Built-in ShopDisplays
- Kiosk Display
- CounterDisplay



Internet access by:



USAGE:

This Android Display can be used in a commercial environment. The Display has Rooted Android operating. This professional display can be used for several solutions to inform / advise people on an attractive way.

SIGNAGE SOFTWARE:

We can provide several kinds of software apps to play your content, remotely controlled, like our "Signage App: control content by f.i. Dropbox and "SbEND signage.

OPTIONAL:

- We can install your software on the devices for larger order quantities.
- Internal memory can be upgraded.
- Similar sizes available: 7 / 10 / 14 / 15.6 / 18.5 / 21.5 / 24 / 27 / 32 / 43 / 55 inch.
- Several kinds of brackets for hangup



Next pages: technical specs and drawing

PRODUCT SHEET

Android Display

24inch Android Touch Display - OS5.1 / 6.0 / 8.1 - RK3288

ArtNr: EL-2402AIO-T

SPECIFICATIONS:

System	CPU	Quad core cortex A17,1.8G,RK3288
	RAM	2GB
	Internal memory	16GB
	Operation system	Android 5.1 / 6.0 /8.1
	Touch screen	10-Point capacitive touch screen
Display	Panel	24"LCD full HD screen,LED backlight
	Resolution	1920*1080
	Active area	527.04(H)x296.46mm(V)
	Display mode	Normally back,IPS
	Viewing angles	89/89(H),89/89(V)
	Contrast ratio	1000
	Luminance	250cdm2
	Aspect Ratio	,16:9
Network	WiFi	802.11b/g/n
	3G dongle	3G USB dongle ext.
	Ethernet	100M/1000M Ethernet
	Bluetooth	Bluetooth 4.0
Interface	Card slot	SD,Support up to 32GB
	USB Device	Mini USB OTG
	USB Hostx2	USB Host 2.0
	Power Jack	DC power input
	RJ45	Ethernet
	HDMI	HDMI output
	Earphone	3.5mm earphone
Media plays	Video format	MPEG-1,MPEG-2,MPEG-4,H.263,H.264,RV etc.,support up to 1080p
	Audio format	MP3/WMA/AAC etc.
	Photo	jpeg
Others	Power consumption	35W
	Wall mounting	VESA,100x100mm
	Speaker	2*3W
	Language	Multi-language
	Working temp	0--40degree
	Certificates	CE/FCC/RoHS
Accessories	Adapter	Adapter,12V,4A
		User manual
		Adapter
		Stand

Unit (Without packaging)			Giftbox (With Packaging)			Carton 2cps/CTN		
L	W	H	L	W	H	L	W	H
580mm	349.2mm	32.5mm	655mm	115mm	455mm	670mm	250mm	480mm
Net(kg)	4.8kg		Net(kg)	6.6kg		Net	13.2kg	
						G.W	14.2kg	

Next page Drawing

PRODUCT SHEET

Android Display

24inch Android Touch Display - OS5.1 / 6.0 / 8.1 - RK3288

ArtNr: EL-2402AIO-T

DRAWINGS

