

Art. EL-2708AIO-T series

ANDROID (non)TOUCH DISPLAYS

AVAILABLE SIZES: 7 - 8 - 10 - 14 - 15.6 - 18.5 - 21.5 - 24 -27 - 32 - 43 - 55inch



RETAIL BUSINESS Android Displays for use in a commercial environment. These displays have a rooted Android operating system and can be used for several solutions to inform and advise people in an attractive way, 24-7.

ONLINE MODELS

Often used in retail displays and built-in ShopDisplays or in Public environments.



TOUCH & PANEL

- 10 points capacitive touch
- Optional: non touch panel
- 27inch High Resolution Panel 1920x1080 pixels



ANDROID CHIP & OS VERSIONS

- RK3288 with Android OS 8 or 10
- RK3399 with Android OS 9, 10 and 12
- RK3568 with Android OS 11



ADDITIONAL FEATURES:

- PoE: Power over Ethernet (8 to 21.5inch)
- NFC & RFID (optional)
- Triggering: pushbuttons, sensors
- LED light: external lightstrips

Note:

There is no signage software installed, please provide your own software or we can provide dedicated signage software.

ANDROID ROOTED

All our models have Rooted Android. The OS system can be adjusted according your needs.

YOUR SOFTWARE

We can pre-install your software apps on the Android OS. We can also make your OS image custommade, with your startup logo.



Easy hangup system at backside (VESA Screw holes plate)



AutoStart by plug in power adapter



WIFI and LAN for internet connection (optional SIM USB dongle)





ANDROID OS

SOFTWARE OPTIONS

ADD: YOUR SOFTWARE

We can pre-install your software apps on the Android OS. We can also make your OS image custommade, with your startup logo.

ADD: SIGNAGE SOFTWARE

We can provide software apps on the Android OS. Find some suggestions below:

KIOWARE: Lockdown your website or your app (kiosk mode)

FULLY VIDEO: AutoStart App loop video from USB & Internal Memory

FULLY WEBSITE: Lockdown your website in full screen mode

ICHANNEL: Remote controlled pushed presentations with web-based control system (CMS). Create in the CMS presentations and schedule them, online.

ROOM & DESK SHARING: Roombooking and Desk Sharing software

Optional: add external Triggers & Sensors for Video Acti-

Customized Android displays to connect triggers for video & volume activation:

- Metal or plastic pushbuttons with lightring and symbol
- Touchless sensor buttons (wave your hand above the sensor)
- RFID Sensors for "Lift and Learn"
- · RFID Sensors for scanning a product with RFID sticker
- Motion detection sensors
- Light Sensors detection area



Optional: add (Interactive) LED Light strips and panels

Customized Android displays to connect LED lightning:

- LED strips or LED Panel Light up your product
- Light up a product during an activated video
- Light up a brand logo in a retail display
- Different colors available



SPECIFICATIONS:


System RAM 2GB Optional 4GB Intenal memory 16GB Optional 3208/64G Operation system Android 11 Touch screen 10-Point capacitive touch screen Parel 271:CD Resolution 1920'1080 Display Mesolution Viewing angles 85/85(1), 85/85(V) Contrast ratio 800 Luminance 250odm2 Aspect Ratio 16:9 Aspect Ratio 16:9 Meri E 802.11b/g/n Bluetooth Bluetooth 4.2 Gard slot SD.support up to 32GB Mini USB USB Pore Jack USB USB Pore Jack Vies format MPS/MALAC etc. Power Jack DC power input R44 MPS/MALAC etc. Media play Vies format Vies format MPS/MALAC etc. Photo piep/ping Vies format MPS/MALAC etc. Micro phone Single pincophone Viespraneu 2/3W <th></th> <th></th> <th colspan="4">CPU</th> <th colspan="5">RK3568 Quad core cortex A55</th>			CPU				RK3568 Quad core cortex A55					
Operation system Android 11 Touch screen 10-Point capacitive touch screen Panel 27LCD Resolution 1920'1080 Display mode Normally black Viewing angles 55/85(H),85/85(V) Contrast ratio 500 Luminance 250cdm2 Aspect Ratio ,16:9 WiFi 802.110/g/n Bluetoth Bluetoth 4.2 Card slot SD.support up to 32GB Mini USB USB Post 2.0 USB USB Host 3.0 USB USB Host 3.0 USB USB Host 3.0 USB nore rack DC power input R445 Ethernet interface HDMI HDMI output Earphone 3.6m earphone Video format MPEC-1,MPEC-4,H.265,H.264,VC-1,VP8,VP9, etc.,support up to 4K Media plays Video format Media ologa Microphone Speaker 2'3W Cother Speaker Cardi sites Carl Sice Cardi getem			RAM									
Touch screen 10-Point capacitive touch screen Panel 27°LCD Resolution 1920°1080 Display mode Normally black Viewing angles 85%5(H),65%5(V) Contrast ratio 500 Luminance 250cdrn2 Aspacet Ratio .16:9 WiFi 802.11bg/n Bluetooth Bluetooth 4.2 Card slot SD,support up to 32GB Mini USB USB host 2.0 Power Jack DC power input R45 Ethernet interface HDMI HDMI output Earphone 3.5mm earphone Video format MPEG-1,MPEG-2,MPEG-4,H.265,H.264,VC-1,VP8,VP9, etc.,support up to 4K Adio format MP3/WMA/AAC etc. Photo jpeg/png Video format MPEG-1,MPEG-2,MPEG-4,H.265,H.264,VC-1,VP8,VP9, etc.,support up to 4K Microphone single microphone Speaker 2/3W Gormat MPEG-1,MPEG-2,MPEG-4,H.265,H.264,VC-1,VP8,VP9, etc.,support up to 4K Microphone single microphone Speaker	Sys	stem										
Panel 27°LCD Resolution 1920'1080 Display mode Normally black. Viewing angles 65/85(1),85/85(V) Contrast ratio 800 Luminance 250cdm2 Aspect Ratio ,16:9 WFi 802.11b/g/n Ethemet 100M/1000M ethemet Buetooth Buetooth 4.2 Gard slot SD.support up to 32GB Mini USB USB OTG USB USB Host 3.0 USB Mol output Earphone 3.5mm earphone Video format MPEG-3.MPEG-4.H.265,H.264,VC-1,VP8,VP9, etc.,support up to 4K Metia plays Nuclo format Photo jpeg/prg Ve												
Pisplay Resolution 1920'1080 Display mode Normally black Display mode Normally black Viewing angles 85/85(H), 85/85(V) Contrast ratio 600 Luminance 250cdm2 Aspect Ratio ,16:9 MrFi 802.11b/g/n Bluetooth Bluetooth 4.2 Card slot SD,support up to 32GB Mini USB USB TOF USB USB Host 3.0 USB USB Host 3.0 USB USB Host 2.0 Power Jack DC power input R43 Ethernet interface HDMI HDMI UPUt Earphone 3.5mm earphone Audio format MPEG-1,MPEG-2,MPEG-4,H.265,H.264,VC-1,VP8,VP9, etc.,support up to 4K Multi-language Microphone Photo jpeg/png VicesA 000x100mm Microphone single microphone Speaker 2?3W Quage Multi-language Working temp 0-40degree <												
Display Display mode Normally black Viewing angles 86/85(H),85/85(V) Contrast ratio 600 Luminance 250cdm2 Aspect Ratio .16:9 WiFi 802.11b/g/n Bluetooth Bluetooth 4.2 Gard slot SD_support up to 32GB Mini USB USB NOTE USB USB NOTE USB USB NotE 2.0 Power Jack DC power input R445 Ethernet HDMI HDMI output Earphone 3.5mm earphone Video format MPEG-1, MPEG-2, MPEG-4, H.265, H.264, VC-1, VP8, VP9, etc., support up to 4K Media plays Video format MPEG-1 JOX Photo jpeg/png VESA 100×100mm Miti-language Multi-language Vorking temp 0-40degree Certificates cerforc Carmara Routine angle 5.0MP VesA Routine angle 5.0MP VesA Routine angle 5.0MP												
Display Viewing angles B5/85(H),85/85(V) Contrast ratio 800 Luminance 250cdm2 Aspect Ratio 16:9 WiFi 802.11b/g/n Biuetooth 800 Biuetooth 802.11b/g/n Card slot SD,support up to 32GB Mini USB USB host 3.0 USB USB host 3.0 USB USB host 2.0 Power Jack Ethernet interface HDMI DC power input RJ45 Ethernet interface HDMI HDMI output Earphone 3.5mm earphone Yideo format MPEG-1,MPEG-2,MPEG-4,H.265,H.264,VC-1,VP8,VP9, etc.,support up to 4K Audio format MPEG-1,MPEG-2,MPEG-4,H.265,H.264,VC-1,VP8,VP9, etc.,support up to 4K Media plays Video format MPEG-1,MPEG-2,MPEG-4,H.265,H.264,VC-1,VP8,VP9, etc.,support up to 4K Media plays Video format MPEG-1,MPEG-2,MPEG-4,H.265,H.264,VC-1,VP8,VP9, etc.,support up to 4K Media plays Video format MPEG-1,MPEG-2,MPEG-4,H.265,H.264,VC-1,VP8,VP9, etc.,support up to 4K Metia plays Multi angle mic												
Contrast ratio B00 Luminance 250cdm2 Aspect Ratio 16:9 WFi 802.11b/g/n Bluetooth 802.11b/g/n Ethernet 100M/1000M ethemet Bluetooth Bluetooth 4.2 Card slot SD_support up to 32GB Mini USB USB Host 3.0 USB USB Host 3.0 USB USB Host 3.0 USB USB Host 2.0 Power Jack DC power input RJ45 Ethernet interface HDMI HDMI output Earphone 3.5mm earphone 3.5mm earphone 3.5mm earphone Yideo format MP3/WMA/AC etc. Photo jpeg/png VESA 100x100mm Microphone single microphone Speaker 2'3'W Working temp 0-40degree Certificates cerf.cc Certificates cerf.cc Certificates cerf.cc Certificates cerf.cc Adapter <td></td>												
Luminance 250cdm2 Aspect Ratio .16:9 WiFi 802.11b/g/n Ethemet 100M/1000M ethemet Bluetooth Bluetooth 4.2 Gard slot SD.support up to 32GB Mini USB USB OTG USB USB Host 3.0 VBB USB host 2.0 Power Jack Dc power input RJ45 Ethemet interface HDMI HDMI output Earphone 3.5mm earphone Video format MPEG-1,MPEG-2,MPEG-4,H.265,H.264,VC-1,VP8,VP9, etc.,support up to 4K Media plays Video format Media plays Video format Video format MPEG-1,MPEG-2,MPEG-4,H.265,H.264,VC-1,VP8,VP9, etc.,support up to 4K Media plays Video format Media plays Video format Media plays Video format Media plays Video format Microphone single microphone Speaker 2'3W User Language Working temp 0-40degree Cirtificates	Dis	splay						85/85(V)				
Aspect Ratio 16:9 WiFi 802.11b/g/n Wetwork Ethemet 100M/1000M ethemet Bluetooth Bluetooth 4.2 Card slot SD_support up to 32GB Mini USB USB OTG USB USB Host 3.0 USB USB Host 3.0 USB DC power input RJ45 Ethemet interface HDMI HDMI output Earphone 3.5mm earphone Video format MPEG-1,MPEG-2,MPEG-4,H.265,H.264,VC-1,VP8,VP9, etc.,support up to 4K Media plays Video format Microphone ipeg/prog VESA 100x100mm Microphone single microphone Speaker 2'3W Cother Language Microphone single microphone Speaker 2'3W Cardiage Multi-language Working temp 0-4/degree Certificates ca/fcc Camera Routine angle 5.0MP User manual yes Adapter			Contrast ra	atio								
Network WiFi 802.11b/g/n Ethernet 100M/1000M ethermet Bluetooth Bluetooth 4.2 Card slot SD,support up to 32GB Mini USB USB OTG USB USB host 3.0 USB USB host 2.0 Power Jack DC power input RJ45 Ethermet interface HDMI HDMI output Earphone 3.5mm earphone Vide format MPEG-1,MPEG-2,MPEG-4,H.265,H.264,VC-1,VP8,VP9, etc.,support up to 4K Media plays Audio format Media plays Vide format Vides of mat MPEG-1,MPEG-2,MPEG-4,H.265,H.264,VC-1,VP8,VP9, etc.,support up to 4K Megin plays Audio format Vide gramet 2"3W Vide format MPEG-1,MPEG-2,MPEG-4,H.265,H.264,VC-1,VP8,VP9, etc.,support up to 4K Mini USB USB for the mathematical state												
Network Ethemet 100M/1000M ethemet Bluetooth Bluetooth 4.2 Card slot SD,support up to 32GB Mini USB USB OTG USB USB Not 3.0 USB USB host 3.0 USB DC power input RJ45 Ethemet interface HDMI HDMI output Earphone 3.5mm earphone Video format MPSG-4,MPCG				tio								
Bluetooth Bluetooth 4.2 Card slot SD.support up to 32GB Mini USB USB OTG USB USB Host 3.0 USB USB host 2.0 Power Jack DC power input RJ45 Ethernet interface HDMI HDMI output Earphone 3.5mm earphone Audio format MPSG-2_MPEG-4,H.265,H.264,VC-1,VP8,VP9, etc.,support up to 4K Media play Video format Media play Video format Media play Video format Mercophone single microphone Speaker 2*3W VESA OutputI-anguage Working temp 0-40degree Certificates celfcc Camera Routine angle 5.0MP Vese manual yes Adapter 12V,4A							802.11b/g	g∕n				
Interface Card slot SD, support up to 32GB Mini USB USB OTG USB USB host 3.0 USB USB host 2.0 Power Jack DC power input RJ45 Ethernet interface HDMI HDMI output Earphone 3.5mm earphone Video format MPEG-1,MPEG-2,MPEG-4,H.265,H.264,VC-1,VP8,VP9, etc.,support up to 4K Audio format MPSWMA/AAC etc. Photo jpeg/png VESA 100x100mm Microphone single microphone Speaker 2*3W Usanguage Multi-language Working temp 0-40degree Certificates ce/fcc Camera Routine angle 5.0MP User manual yes Adapter 12V,4A	Net	work										
Mini USB USB OTG USB USB Host 3.0 USB USB host 2.0 Power Jack DC power input RJ45 Ethernet interface HDMI HDMI output Earphone 3.5mm earphone Video format MPEG-1,MPEG-2,MPEG-4,H.265,H.264,VC-1,VP8,VP9, etc.,support up to 4K Audio format MP3/WMA/AAC etc. Photo jpeg/png VESA 100x100mm Microphone sigle microphone Speaker 2*3W Cother Enguage Working temp 0-40degree Certificates celfcc Camera Routine angle 5.0MP User manual yes Adapter 12V,4A			Bluetooth									
Interface USB USB Host 3.0 IUSB USB host 2.0 Power Jack DC power input RJ45 Ethernet interface HDMI HDMI output Earphone 3.5mm earphone Video format MPEG-1,MPEG-2,MPEG-4,H.265,H.264,VC-1,VP8,VP9, etc.,support up to 4K Audio format MP3/WMA/AAC etc. Photo jpeg/png VESA 100x100mm Microphone single microphone Speaker 2*3W Verking temp 0-40degree Certificates ce/fcc Camera Routine angle 5.0MP User manual yes Adapter 12V,4A									B			
Interface USB USB host 2.0 Power Jack DC power input RJ45 Ethernet interface HDMI HDMI output Earphone 3.5mm earphone Video format MPEG-1,MPEG-2,MPEG-4,H.265,H.264,VC-1,VP8,VP9, etc.,support up to 4K Audio format MP3/WMA/AAC etc. Photo jpeg/png VESA 100x100mm Microphone single microphone Speaker 2*3W Cettificates cet/fcc Camera Multi-language Working temp 0-40degree Cettificates cet/fcc Camera Routine angle 5.0MP User manual yes Adapter 12V,4A												
Power Jack DC power input RJ45 Ethernet interface HDM HDM output Earphone 3.5mm earphone Video format MPEG-1,MPEG-2,MPEG-4,H.265,H.264,VC-1,VP8,VP9, etc.,support up to 4K Audio format MP3/WMA/AAC etc. Photo jpeg/png VESA 100x100mm Microphone single microphone Speaker 2*3W Cother Language Working temp 0-40degree Certificates ce/fcc Camera Routine angle 5.0MP User manual yes Adapter 12V,4A												
Power Jack DC power input RJ45 Ethernet interface HDMI HDMI output Earphone 3.5mm earphone Video format MPEG-1,MPEG-2,MPEG-4,H.265,H.264,VC-1,VP8,VP9, etc.,support up to 4K Audio format MP3/WMA/AAC etc. Photo jpeg/png VESA 100x100mm Microphone single microphone Speaker 2*3W Chrifticates ce/fcc Camera Routine angle 5.0MP User manual yes Adapter 12V,4A	Into	orface										
HDMI HDMI output Earphone 3.5mm earphone Video format MPEG-1,MPEG-2,MPEG-4,H.265,H.264,VC-1,VP8,VP9, etc.,support up to 4K Audio format MP3/WMA/AAC etc. Photo jpeg/png VESA 100x100mm Microphone single microphone Speaker 2*3W Verking temp 0-40degree Certificates ceftcc Camera Routine angle 5.0MP User manual yes Adapter 12V,4A	inte	illace		k			DC power	r input				
Earphone 3.5mm earphone Video format MPEG-1,MPEG-2,MPEG-4,H.265,H.264,VC-1,VP8,VP9, etc.,support up to 4K Audio format MP3/WMA/AAC etc. Photo jpeg/png VESA 100x100mm Microphone single microphone Speaker 2*3W Vorking temp 0-40degree Certificates ceftcc Camera Routine angle 5.0MP User manual yes Adapter 12V,4A												
Video format MPEG-1,MPEG-2,MPEG-4,H.265,H.264,VC-1,VP8,VP9, etc.,support up to 4K Audio format MP3/WMA/AAC etc. Photo jpeg/png VESA 100x100mm Microphone single microphone Speaker 2*3W Verking temp 0-40degree Certificates ce/fcc Camera Routine angle 5.0MP User manual yes Adapter 12V,4A			HDMI									
Media plays Audio format MP3/WMA/AAC etc. Photo jpeg/png VESA 100x100mm Microphone single microphone Speaker 2*3W Language Multi-language Working temp 0-40degree Certificates ce/fcc Camera Routine angle 5.0MP User manual yes Adapter 12V,4A												
Photo jpeg/png VESA 100x100mm Microphone single microphone Speaker 2*3W Language Multi-language Working temp 0-40degree Certificates ce/fcc Camera Routine angle 5.0MP User manual yes Adapter 12V,4A									PEG-4,H.26	5,H.264,VC-1,VP8,VP9, etc.,support up to 4K		
VESA 100x100mm Microphone single microphone Speaker 2*3W Language Multi-language Working temp 0-40degree Certificates ce/fcc Camera Routine angle 5.0MP User manual yes Adapter 12V,4A	Media	a plays		at				A/AAC etc.				
Microphone single microphone Speaker 2*3W Language Multi-language Working temp 0-40degree Certificates cefcc Camera Routine angle 5.0MP User manual yes Adapter 12V,4A												
Speaker 2*3W Other Language Multi-language Working temp 0-40degree Certificates ceffcc Camera Routine angle 5.0MP User manual yes Adapter 12V,4A												
Other Language Multi-language Working temp 0-40degree Certificates ce/fcc Camera Routine angle 5.0MP User manual yes Adapter 12V,4A				e				crophone				
Working temp 0-40degree Certificates ce/fcc Camera Routine angle 5.0MP User manual yes Adapter 12V,4A												
Certificates ce/fcc Camera Routine angle 5.0MP User manual yes Adapter 12V,4A	Oth	ner					Multi-lang	Juage				
Camera Routine angle 5.0MP User manual yes Adapter 12V,4A								ee				
User manual yes Adapter 12V,4A				S								
Adapter 12V,4A								ingle 5.0MF				
				ıal								
Accessories Stand yes												
	Acces	ssories	Stand				yes					
	oduct M	ossuromon	mm							7		
oduct Measurement mm						Carton2n	Carton2pcs /CTN					
			у н						н	-		
oduct Measurement, mm Giftbox (With Packaging) Carton2pcs /CTN it (Without packaging) W H W					**					-		
			+		1.		N1-4	1	-	-		
uit (Without packaging) Giftbox (With Packaging) Carton2pcs /CTN L W H L W	et(kg)	lka		Not(ka)								








ANDROID OS

DRAWING:









ANDROID OS

OTHER MODEL TYPES

OPEN FRAME



NARROW BEZEL



STRETCHED LCD



ROOM BOOKING



Constants with (

DESK SHAPE



HEALTH CARE



FLOOR KIOSK



HANGING LCD

