# PRODUCT SHEET

# 24inch Android Touch Display - HD

ArtNr: EL-2401AIO-T

#### **MAIN FEATURES:**

- AutoStart by plug in power-adapter
- LCD panel 1920\*1080 pixels
- 10points Capacitive Touchscreen
- Internal HD videoplayer 1080P
- **ROOTED Android 4.4.2**
- Internet access by WIFI / LAN (opt. 3G)
- Internal Speakers
- 3.5mm Jack output
- Thin housing
- Power adapter with 3meter cable
- Usage up to 24 hours per day
- ScrewHoles for hangup / built-in

#### **MAIN PURPOSE:**

- Digital Signage Display
- Advertisement Display
- Built-in ShopDisplays
- Kiosk Display
- CounterDisplay

#### **USAGE:**

This Android Display can be used in a commercial environment. The Display has **Rooted** Android 4.4.2 operating system and comes with a capactive touch front layer. This professional display can be used for several solutions to inform / advise people on an attractive way.

#### SIGNAGE SOFTWARE:

We can provide several kinds of software apps to play your content, remotely controlled, like our "Signage App: control content by f.i. Dropbox and "SbEND signage.

#### **OPTIONAL**

- We can install your software on the devices for larger order quantities.
- Internal memory can be upgraded.
- Similar sizes available: 7 / 10 / 14 / 15.6 / 18.5 / 21.5 / 24 / 27 / 32 inch.
- Several kinds of brackets for hangup












































Next pages: technical specs and drawing

# PRODUCT SHEET **24inch Android Touch Display – HD**

ArtNr: EL-2401AIO-T

## **SPECIFICATIONS**

System	CPU	Quad core cortex A9,1.6G,RK3188	
	RAM	1GB	
	Internal memory	8GB	
	Operation system	Android 4.4.2 - ROOTED	
	Startup	Autostart by plugin powercable	
	Touch screen	10-Point capacitive touch screen	
Display	Panel	24"LCD full HD screen,LED backlight	
	Resolution	1920*1080	
	Viewing angles	85/85(H),80/80(V)	
Display	Contrast ratio	1000	
	Luminance	250cdm2	
	Aspect Ratio	16:9	
Network	WiFi	802.11b/g/n	
	3G dongle	3G USB dongle ext.	
	Ethernet	10M/100M Ethernet	
	Bluetooth	Bluetooth	
	Card slot	SD,Support up to 32GB	
	USB Device	Mini USB OTG	
Interface	USB Hostx3	USB Host 2.0	
Interface	Power Jack	DC power input - AutoStart-Play	
	RJ45	Ethernet	
	Earphone	3.5mm earphone	
	Video format	MPEG-1,MPEG-2,MPEG-4,H.263,H.264,RV etc.,support up to 1080p	
Media plays	Audio format	MP3/WMA/AAC etc.	
	Photo	jpeg	
	Power consumption	35W	
	Wall mounting	VESA,100x100mm	
	Speaker	2*3W	
Others	Camera	5.0M/P,AF	
	Language	Multi-language	
	Application	MSN/Skype/Facebook/Twitter/Youtube/E-mail/google map etc	
	Adapter	Adapter,12V,4A	
Accessories	User manual		
	Adapter		
	Stand		
	SD/USB protect cover		

Product Measurement, mm											
Unit (Without packaging)			Giftbox (With Packaging)			Carton 2pcs /CTN					
L	W	Н	L	W	Н	L	W	Н			
580mm	32.5mm	375mm	655mm	115mm	455mm	670mm	250mm	480mm			
Net(kg)	4.8		Net(kg)	6.5kg		Net	13kg				
		G.W	14kg								

Next page: Drawing

ArtNr: EL-2401AIO-T

## **DRAWING**

