PRODUCT SHEET

27inch Android Touch Display - HD

ArtNr: EL-2701AIO-T

MAIN FEATURES:

- AutoStart by plug in power-adapter
- LCD panel 1920*1080 pixels
- 10points Capacitive Touchscreen
- Internal HD videoplayer 1080P
- **ROOTED Android 4.4.2**
- Internet access by WIFI / LAN (opt. 3G)
- Internal Speakers
- 3.5mm Jack output
- Thin housing
- Power adapter with 3meter cable
- Usage up to 24 hours per day
- ScrewHoles for hangup / built-in

MAIN PURPOSE:

- Digital Signage Display
- Advertisement Display
- Built-in ShopDisplays
- Kiosk Display
- CounterDisplay

USAGE:

This Android Display can be used in a commercial environment. The Display has **Rooted** Android 4.4.2 operating system and comes with a capactive touch front layer. This professional display can be used for several solutions to inform / advise people on an attractive way.

SIGNAGE SOFTWARE:

We can provide several kinds of software apps to play your content, remotely controlled, like our "Signage App: control content by f.i. Dropbox and "SbEND signage.

OPTIONAL

- We can install your software on the devices for larger order quantities.
- Similar sizes available: 7 / 10 / 14 / 15.6 / 18.5 / 21.5 / 24 / 27 / 32 inch.
- Internal memory can be upgraded.
- Several kinds of brackets for hangup


















Internet access by:























Next pages: technical specs and drawing

PRODUCT SHEET 27inch Android Touch Display – HD

ArtNr: EL-2701AIO-T

SPECIFICATIONS

System	CPU	Quad core cortex A9,1.6G,RK3188		
	RAM	1GB		
	Internal memory	8GB		
	Operation system	Android 4.4.2 - ROOTED		
	Startup	AutoStart by plugin powercable		
	Touch screen	10-Point capacitive touch screen		
	Panel	27"LCD full HD screen,LED backlight		
	Resolution	1920*1080		
Diaglay	Viewing angles	85/85(H),80/80(V)		
Display	Contrast ratio	1000		
	Luminance	250cdm2		
	Aspect Ratio	16:9		
Network	WiFi	802.11b/g/n		
	3G dongle	3G USB dongle ext.		
	Ethernet	10M/100M Ethernet		
	Bluetooth	Bluetooth		
	Card slot	SD,Support up to 32GB		
	USB Device	Mini USB OTG		
Interface	USB Hostx3	USB Host 2.0		
IIILEHACE	Power Jack	DC power input - AUTO-start-play		
	RJ45	Ethernet		
	Earphone	3.5mm earphone		
	Video format	MPEG-1,MPEG-2,MPEG-4,H.263,H.264,RV etc.,support up to 1080p		
Media plays	Audio format	MP3/WMA/AAC etc.		
	Photo	jpeg		
	Power consumption	40W		
	Wall mounting	VESA,100x100mm		
	Speaker	2*3W		
Others	Camera	5.0M/P,AF		
	Language	Multi-language		
	Application	MSN/Skype/Facebook/Twitter/Youtube/E-mail/google map etc		
	Adapter	Adapter,12V,4A		
Accessories	User manual			
	Adapter			
	Stand			
	SD/USB protect cover			

Product Measurement, mm										
Unit (Without packaging)			Giftbox (With Packaging)			Carton 2pcs /CTN				
L	W	Τ	L	W	Ι	L	W	Н		
653mm	32.5mm	420mm	725mm	115mm	490mm	740mm	250mm	515mm		
Net(kg)	5.2kg		Net(kg)	7.1kg		Net	14.2kg			
			_			G.W	15.4kg			

Next page: Drawing

ArtNr: EL-2701AIO-T

DRAWING

