### PRODUCT SHEET

## Android Display

## 27inch Android Non Touch Display - OS5.1 / 6.0 / 8.1 - RK3288

ArtNr: EL-2702AIO

#### MAIN FEATURES:

- AutoStart by plug in power-adapter
- LCD panel 1920x1080 pixels
- Internal HD videoplaver 1080P
- Rooted Android 5.1 / 6.0 / 8.1 RK3288
- Internet access by WIFI / LAN (opt. 3G)
- Internal Speakers 2x2 W
- 3.5mm Jack output
- Thin housing
- Remote Control
- Power adapter with 3meter cable
- Usage up to 24 hours per day
- Screw Holes for hangup / built-in



- Digital Signage Display
- Advertisement Display
- Built-in ShopDisplays
- Kiosk Display
- CounterDisplay



This Android Display can be used in a commercial environment. The Display has Rooted Android operating. This professional display can be used for several solutions to inform / advise people in an attractive way.

#### SIGNAGE SOFTWARE:

We can provide several kinds of software apps to play your content, remotely controlled, like our "Signage App: control content by f.i. Dropbox and "SbEND signage.

#### **OPTIONAL:**

- We can install your software on the devices for larger order quantities.
- Internal Memory can be upgraded.
- Similar sizes available: 7 / 10 / 14 / 15.6 / 18.5 / 21.5 / 24 / 27 / 32 / 43 / 55 inch.
- Several kinds of brackets for hangup.















#### Internet access by:


























# PRODUCT SHEET Android Display 27inch Android Non Touch Display - OS5.1 / 6.0 / 8.1 - RK3288

ArtNr: EL-2702AIO

#### SPECIFICATIONS:

System	CPU	Quad core cortex A17,1.8G,RK3288
	RAM	2GB
	Internal memory	16GB
	Operation system	Android 5.1 / 6.0 / 8.1
	Touch screen	Non Touch
,	Panel	27"LCD full HD screen,LED backlight
	Resolution	1920*1080
	Active area	597.6(H)X336.15mm(V)
Display	Display mode	Normally black,IPS
Display	Viewing angles	89/89(H),89/89(V)
	Contrast ratio	1000
	Luminance	250cdm2
	Aspect Ratio	,16:9
	WiFi	802.11b/g/n
Network	3G dongle	3G USB dongle ext.
Network	Ethernet	100M/1000M Ethernet
	Bluetooth	Bluetooth 4.0
	Card slot	SD,Support up to 32GB
	USB Device	Mini USB OTG
	USB Hostx2	USB Host 2.0
Interface	Power Jack	DC power input
	RJ45	Ethernet
	HDMI	HDMI output
	Earphone	3.5mm earphone
	Video format	MPEG-1,MPEG-2,MPEG-4,H.263,H.264,RV etc.,support up to 1080r
Media plays	Audio format	MP3/WMA/AAC etc.
	Photo	jpeg
	Power consumption	40W
	Wall mounting	VESA,100x100mm
Others	Speaker	2*3W
	Language	Multi-language
	Working temp	040degree
	Certificates	CE/FCC/RoHS
	Adapter	Adapter,12V,4A
		User manual
		Adapter
Accessories		Stand

Product Measurement, mm											
Unit (without packaging)			Giftbox (With Packaging) 1pc			Carton 2pc/ctn					
L	W	Н	L	W	Н	L	W	Н			
653 mm	32.5 mm	420 mm	725 mm	115mm	490 mm	740 mm	250 mm	515 mm			
Net(kg) 5.2			Net(kg) 7.1			Net(kg) 14.2					

G.W. 15.4

27inch Android Non Touch Display - OS5.1 / 6.0 / 8.1 - RK3288

ArtNr: EL-2702AIO

