

PRODUCT SHEET

Android Display

43inch Android Touch Display - OS7.1 / 9.0 - RK3399

ArtNr: EL-4303AIO-T

MAIN FEATURES:

- 10 points Capacitive Touchscreen
- AutoStart by plug in power-adapter
- LCD panel 1920*1080 pixels - IPS
- Internal HD videoplayer 1080P
- Rooted Android 7.1 / 9.0 - RK3399
- Internet access by WIFI /LAN (opt. 3G)
- Internal Speakers
- 3.5mm Jack output
- Thin housing
- Power adapter with 3meter cable
- Usage up to 24 hours per day
- ScrewHoles for hangup / built-in




MAIN PURPOSE:

- Digital Signage Display
- Advertisement Display
- Built-in ShopDisplays
- Kiosk Display
- CounterDisplay



Internet access by:



USAGE:

This Android Display can be used in a commercial environment. The Display has Rooted Android operating. This professional display can be used for several solutions to inform / advise people on an attractive way.

SIGNAGE SOFTWARE:

We can provide several kinds of software apps to play your content, remotely controlled, like our "Signage App: control content by f.i. Dropbox and "SbEND signage.

OPTIONAL:

- We can install your software on the devices for larger order quantities.
- Internal memory can be upgraded.
- Similar sizes available: 14 / 15.6 / 18.5 / 21.5 / 24 / 27 / 32 / 43 / 55 inch.
- Several kinds of brackets for hangup



Next pages: technical specs and drawing

PRODUCT SHEET

Android Display

43inch Android Touch Display - OS7.1 / 9.0 - RK3399

ArtNr: EL-4303AIO-T

SPECIFICATIONS

System	CPU	Dual-core A72+quad-core A53,2.0G,RK3399
	RAM	2GB
	Internal memory	16GB
	Operation system	Android 7.1 / 9.0
	Touch screen	10-Point capacitive touch screen
Display	Panel	43"LCD full HD IPS screen,LED backlight
	Resolution	1920*1080
	Active area,diagonal	1094.96mm
	Display mode	Normally black,IPS
	Viewing angles	89/89(H),89/89(V)
	Contrast ratio	1200
	Luminance	300cdm2
	Aspect Ratio	,16:9
Network	WiFi	802.11b/g/n/ac, 2.4G+5G
	3G dongle	3G USB dongle ext.
	Ethernet	100M/1000M Ethernet
	Bluetooth	Bluetooth 4.0
Interface	Card slot	SD,Support up to 32GB
	USB Device	Mini USB OTG
	USB Hostx2	USB Host 2.0
	RJ45	Ethernet
	HDMI	HDMI output
Media plays	Earphone	3.5mm earphone
	Video format	MPEG-1,MPEG-2,MPEG-4,H.263,H.264,RV etc.,support up to 1080p
	Audio format	MP3/WMA/AAC etc.
Others	Photo	jpeg
	Power consumption	100W
	Wall mounting	VESA,400x400mm
	Speaker	2*5W
	Language	Multi-language
	Working temp	0--40degree
	Certificate	CE/FCC/RoHS
Accessories	Power	AC100V-240V input
		User manual

Unit (Without packaging)			Giftbox (With Packaging)			Carton 1PCS		
L	W	H	L	W	H	L	W	H
995.28mm	592.14mm	55.6mm	1156mm	160mm	792mm	1180mm	178mm	817mm
Net(kg)	17.85kg		Net(kg)	21.05kg		Net		
						G.W		

Next page Drawing

PRODUCT SHEET

Android Display

43inch Android Touch Display - OS7.1 / 9.0 - RK3399

ArtNr: EL-4303AIO-T

DRAWINGS

