PRODUCT SHEET

Android Display

55inch Android Non Touch Display - OS5.1 / 6.0 / 8.1 - RK3288

ArtNr: EL-5502AIO

MAIN FEATURES:

- AutoStart by plug in power-adapter
- LCD panel 1920x1080 pixels
- Internal HD videoplayer 1080P
- Rooted Android 5.1 / 6.0 / 8.1 RK3288
- Internet access by WIFI / LAN (opt. 3G)
- Internal Speakers 2x2 W
- 3.5mm Jack output
- Thin housing
- Remote Control
- Power adapter with 3meter cable
- Usage up to 24 hours per day
- Screw Holes for hangup / built-in

MAIN PURPOSE:

- Digital Signage Display
- Advertisement Display
- Built-in ShopDisplays
- Kiosk Display
- CounterDisplay

USAGE:

This Android Display can be used in a commercial environment. The Display has Rooted Android operating. This professional display can be used for several solutions to inform / advise people in an attractive way.

SIGNAGE SOFTWARE:

We can provide several kinds of software apps to play your content, remotely controlled, like our "Signage App: control content by f.i. Dropbox and "SbEND signage.

OPTIONAL:

- We can install your software on the devices for larger order quantities.
- Internal Memory can be upgraded.
- Similar sizes available: 7 / 10 / 14 / 15.6 / 18.5 / 21.5 / 24 / 27 / 32 / 43 / 55 inch.
- Several kinds of brackets for hangup.

























Internet access by:











Next pages: technical specs and drawing

PRODUCT SHEET Android Display 55inch Android Non Touch Display - OS5.1 / 6.0 / 8.1 - RK3288

ArtNr: EL-5502AIO

SPECIFICATIONS:

RAM		CPU	Quad core cortex A17,1.8G,RK3288
Internal memory	System	RAM	2GB
Touch screen		Internal memory	16GB
Screen S5" 4K screen		Operation system	Android 5.1 / 6.0 / 8.1
Resolution 3840*2160		Touch screen	Non Touch
Display mode		Screen	55" 4K screen
Active area 1387.8mm,diagonal		Resolution	3840*2160
Active area 1387.8mm,diagonal		Display mode	Normally black,IPS
Viewing angles			
Contrast ratio	Display	Viewing angles	
Display mode			
Display mode		Luminance	
Aspect Ratio ,16:9		Display mode	
Network Ethernet 100M/1000M Ethernet 100M/100M 10			
Network	Network		
Bluetooth Bluetooth 4.0			
Card slot			
USB Device Mini USB OTG			
USB Hostx2			
RJ45			
HDMI	Interface		
Earphone 3.5mm earphone			
Media plays Video format MPEG-1,MPEG-2,MPEG-4,H.263,H.264,RV etc.,support up to 1080pt Audio format MP3/WMA/AAC etc. Photo jpeg Power consumption 120W Wall mounting VESA,400x400mm Speaker 2*5W Language Multi-language Working temp 040degree Certificates CE/FCC/RoHS Power AC100-240V User manual			
Media plays Audio format MP3/WMA/AAC etc. Photo jpeg Power consumption 120W Wall mounting VESA,400x400mm Speaker 2*5W Language Multi-language Working temp 040degree Certificates CE/FCC/RoHS Power AC100-240V User manual		· ·	
Photo jpeg	Media plavs		
Power consumption 120W			
Wall mounting VESA,400x400mm Speaker 2*5W Language Multi-language Working temp 040degree Certificates CE/FCC/RoHS Power AC100-240V User manual	Others	Power consumption	
Others Speaker 2*5W Language Multi-language Working temp 040degree Certificates CE/FCC/RoHS Power AC100-240V User manual			VESA.400x400mm
Others Language Multi-language Working temp 040degree Certificates CE/FCC/RoHS Power AC100-240V User manual			,
Working temp O40degree Certificates CE/FCC/RoHS Power AC100-240V User manual		•	
Certificates CE/FCC/RoHS Power AC100-240V User manual			
Power AC100-240V User manual			
User manual User manual			
			SSS. HMHMMI
Accessories	Accessories		
	7.00000030		

Product M	Product Measurement, mm											
Unit (without packaging)			Giftbox (With Packaging) 1pc			Carton 5pc/ctn						
L	W	Н	L W H			L	W	Н				
1263.18	747.28	55.5										
mm	mm	mm										
Net(kg)	Net(kg)		Net(kg)			Net(kg)						

G.W.

55inch Android Non Touch Display - OS5.1 / 6.0 / 8.1 - RK3288

ArtNr: EL-5502AIO

DRAWINGS:

