# PRODUCT SHEET Android Counter Display 17.3inch Android Display Touch - OS8.1 - RK3288 ArtNr: EL-1712AIO-T-CD

MAIN FEATURES:

- Capacitive Touchscreen
- LCD panel 1920x1080 pixels
- Internal HD videoplayer 1080P
- CounterStand
- Rooted Android 5.1/6.0/8.1
- Chip RK3288
- Internet access by WIFI + LAN (opt. 3G)
- Internal Speakers 2 x 1 W
- 3.5mm Jack output
- Thin housing
- USB host
- Power adapter with 3meter cable
- Usage up to 24 hours per day

#### MAIN PURPOSE:

- Digital Signage Display
- Advertisement Display
- Built-in ShopDisplays
- Kiosk Display
- CounterDisplay





Internet access by:





This Android Display can be used in a commercial environment. The Display has Rooted Android operating. This professional display can be used for several solutions to inform / advise people in an attractive way.

### SIGNAGE SOFTWARE:

We can provide several kinds of software apps to play your content, remotely controlled, like our "Signage App: control content by f.i. Dropbox and "SbEND signage.

## OPTIONAL:

- We can install your software on the devices for larger order quantities.
- Internal Memory can be upgraded.
- Similar sizes available: 7 / 10.1 / 13.3 / 15.6inch.
- Non Touch
- NFC RFID
- Internal Battery
- PoE Function



Next pages: technical specs and drawing

All rights reserved. Changes to specifications and descriptions may be made at any time without prior notice.



## PRODUCT SHEET Android Counter Display 17.3inch Android Display Touch - OS8.1 - RK3288 ArtNr: EL-1712AIO-T-CD

### SPECIFICATIONS:

n	RAM nternal mem Operation sy Fouch scree Panel Resolution Active area Display mod Viewing angl Viewing angl Contrast ratii Luminance Aspect Ratic WiFi Ethernet Buletooth Card slot JSB x 2 Micro USB HDMI RJ45 Serial port	stem n e e o			17.3"LCD II 1920*1080 381.89(H)x Normally bl 85/85/85/85 800 250cd/m2 ,16:9 802.11b/g/r 100M/1000 Bluetooth 4 TF card USB Host	apacitive tou IPS panel (214.81mm(\ olack ,IPS 5(L/R/U/D) n N ethernet						
y 	Dperation sy Fouch scree Panel Resolution Active area Display mod Viewing angl Contrast rati Luminance Aspect Ratic WiFi Ethernet Buletooth Card slot JSB x 2 Micro USB HDMI RJ45	stem n e e o			Android 8.1 10-Point ca 17.3"LCD II 1920*1080 381.89(H)x Normally bl 85/85/85/85 800 250cd/m2 ,16:9 802.11b/g/r 100M/1000 Bluetooth 4 TF card USB Host	apacitive tou IPS panel (214.81mm(\ olack ,IPS 5(L/R/U/D) n N ethernet						
y	Fouch scree Panel Resolution Active area Display mod Viewing angl Contrast ratii Luminance Aspect Ratic WiFi Ethernet Buletooth Card slot JSB x 2 Vicro USB HDMI RJ45	n e e o			10-Point ca 17.3"LCD II 1920*1080 381.89(H)x Normally bl 85/85/85/85 800 250cd/m2 ,16:9 802.11b/g/r 100M/1000 Bluetooth 4 TF card USB Host	apacitive tou IPS panel (214.81mm(\ olack ,IPS 5(L/R/U/D) n N ethernet						
y	Panel Resolution Active area Display mod Viewing angl Contrast ratii- uminance Aspect Ratic WiFi Ethernet Buletooth Card slot JSB x 2 Wicro USB HDMI RJ45	e e o			17.3"LCD II 1920*1080 381.89(H)x Normally bl 85/85/85/85 800 250cd/m2 ,16:9 802.11b/g/r 100M/1000 Bluetooth 4 TF card USB Host	n NES panel k214.81mm(\ alack ,IPS 5(L/R/U/D) n NM ethernet						
y	Panel Resolution Active area Display mod Viewing angl Contrast ratii- uminance Aspect Ratic WiFi Ethernet Buletooth Card slot JSB x 2 Wicro USB HDMI RJ45	e e o			1920*1080 381.89(H)x Normally bl 85/85/85/85 800 250cd/m2 ,16:9 802.11b/g/r 100M/1000 Bluetooth 4 TF card USB Host	x214.81mm(\ black ,IPS 5(L/R/U/D) n 0M ethernet	V)					
y	Resolution Active area Display mod Viewing angl Contrast ratii Luminance Aspect Ratic WiFi Ethernet Buletooth Card slot JSB x 2 Micro USB HDMI RJ45	e 0			1920*1080 381.89(H)x Normally bl 85/85/85/85 800 250cd/m2 ,16:9 802.11b/g/r 100M/1000 Bluetooth 4 TF card USB Host	x214.81mm(\ black ,IPS 5(L/R/U/D) n 0M ethernet	V)					
y	Active area Display mod Viewing angl Contrast ratii Luminance Aspect Ratic WiFi Ethernet Buletooth Card slot JSB x 2 Micro USB HDMI RJ45	e 0			381.89(H)x Normally bl 85/85/85/85 800 250cd/m2 ,16:9 802.11b/g/r 100M/1000 Bluetooth 4 TF card USB Host	x214.81mm(\ black ,IPS 5(L/R/U/D) n DM ethernet	V)					
y	Display mod Viewing angl Contrast ratii Luminance Aspect Ratic WiFi Ethernet Buletooth Card slot JSB x 2 Viicro USB HDMI RJ45	e 0			Normally bl 85/85/85/85 800 250cd/m2 ,16:9 802.11b/g/r 100M/1000 Bluetooth 4 TF card USB Host	n Diack ,IPS 5(L/R/U/D) n DM ethernet						
y	Viewing angl Contrast ratii Luminance Aspect Ratic WiFi Ethernet Buletooth Card slot JSB x 2 Micro USB HDMI RJ45	e 0			85/85/85/85 800 250cd/m2 ,16:9 802.11b/g/r 100M/1000 Bluetooth 4 TF card USB Host	5(L/R/U/D) n DM ethernet						
	Contrast rati Luminance Aspect Ratic WiFi Ethernet Buletooth Card slot JSB x 2 Micro USB HDMI RJ45	0			800 250cd/m2 ,16:9 802.11b/g/r 100M/1000 Bluetooth 4 TF card USB Host	n DM ethernet						
	Luminance Aspect Ratic WiFi Ethernet Buletooth Card slot JSB x 2 Micro USB HDMI RJ45				250cd/m2 ,16:9 802.11b/g/r 100M/1000 Bluetooth 4 TF card USB Host	M ethernet						
k ;e	Aspect Ratic ViFi Ethernet Buletooth Card slot JSB x 2 Vicro USB HDMI RJ45				,16:9 802.11b/g/r 100M/1000 Bluetooth 4 TF card USB Host	M ethernet						
:k	WiFi Ethernet Buletooth Card slot JSB x 2 Micro USB HDMI RJ45				802.11b/g/r 100M/1000 Bluetooth 4 TF card USB Host	M ethernet						
k	Ethernet Buletooth Card slot JSB x 2 Micro USB HDMI RJ45				100M/1000 Bluetooth 4 TF card USB Host	M ethernet						
2e	Buletooth Card slot JSB x 2 Micro USB HDMI RJ45				Bluetooth 4 TF card USB Host							
;e -	Card slot JSB x 2 Micro USB HDMI RJ45				TF card USB Host	+.0						
<b>:e</b>	JSB x 2 Micro USB HDMI RJ45				USB Host							
;e	Micro USB HDMI RJ45											
e -	HDMI RJ45											
e	RJ45							Micro USB OTG				
						HDMI output, support 4K						
	Serial port					RJ45						
					USB for serial port, RS232							
		Power jack				DC power input						
	Earphone				3.5mm earphone							
	Video format				MPEG-1,MPEG-2,MPEG-4,H.263,H.264,VC1,RV etc.,support up to 4Kx2K							
- P	Audio format				MP3/WMA/AAC etc.							
	Photo				jpeg							
	Battery				Optional							
	NFC					,NFC 13.56	MHz, ISO14	4443A/ISO14443B/ISO 15693/Mifare classic/Sony felica				
	Speaker				2*2W							
· l	Camera											
	MIC				Built-in MIC							
	Language											
						Adapter, 12V/2A						
Accessories		User manual				yes						
	m											
				170mm			350mm					
14kg		Net(kg)	3.24kg		Net	4.2kg						
					G.W							
ac 38	ement, m kaging) W 8.03mm	Speaker Camera MIC Power consu Language Adapter User manual ement, mm skaging) W H 3.03mm 152.95mm	Speaker Camera MIC Power consumption Language Adapter User manual ement, mm skaging) Giftbox (W W H L 3.03mm 152.95mm 492mm	Speaker   Camera   MIC   Power consumption   Language   Adapter   User manual   ement, mm   skaging) Giftbox (With Packagir   W H L W   8.03mm 152.95mm 492mm 330mm	Speaker   Camera   MIC   Power consumption   Language   Adapter   User manual   ement, mm   skaging) Giftbox (With Packaging)   W H L W   8.03mm 152.95mm 492mm 330mm 170mm	Speaker 2*2W   Camera 2.0M/P,Frc   MIC Built-in MIC   Power consumption 20W   Language Multi-langu   Adapter Adapter, 12   User manual yes   ement, mm Staging) Giftbox (With Packaging) Carton pcs   W H L W H L   8.03mm 152.95mm 492mm 330mm 170mm 507mm	Speaker 2*2W   Camera 2.0M/P,Front camera   MIC Built-in MIC   Power consumption 20W   Language Multi-language   Adapter Adapter,12V/2A   es User manual yes   ement, mm Staging) Giftbox (With Packaging) Carton pcs/CTN   W H L W H L   3.03mm 152.95mm 492mm 330mm 170mm 507mm 358mm   kg Net(kg) 3.24kg Net 4.2kg 4.2kg	Speaker   2*2W     Camera   2.0M/P,Front camera     MIC   Built-in MIC     Power consumption   20W     Language   Multi-language     Adapter   Adapter,12V/2A     User manual   yes     ement, mm      Skaging)   Giftbox (With Packaging)   Carton pcs/CTN     W   H   L   W   H     8.03mm   152.95mm   492mm   330mm   170mm   507mm   358mm   350mm     kg   Net(kg)   3.24kg   Net   4.2kg   4.2kg   4.2kg				

## PRODUCT SHEET Android Counter Display 17.3inch Android Display Touch - OS8.1 - RK3288 ArtNr: EL-1712AIO-T-CD

DRAWINGS:



